

Frame Out™ Stem

FRAMED EXIT SIGN

TYPE
PROJECT

Overview

- The aluminum frame minimizes light projection at the edge of the sign. Frame Out with stem comes with a canopy cover and four 12" stems that can be screwed together for a one to four foot drop. Custom stem lengths are also available. In addition to white, black, and silver, the sign can be specified in anodized, plated, woodgrain, and custom RAL-matched finishes—flexibility that permits better visual integration into the interior environment.
- Designed with architects, engineers, and lighting designers in mind
- All-aluminum extruded housing with high-grade acrylic face
- Removable front cover for easy installation
- Optional 6" or 8" lettering in red or green
- Field-adjustable arrows for left, right, or dual directions
- Dual Voltage 120v/277v AC with long-life LED illumination
- Easily accessible test switch and charge rate indicator
- UL 924, NEC, OSHA, and NFPA 101 Life Safety Code approved
- Listed for damp locations
- Developed in collaboration with Gensler serving as product design consultant
- North America/Europe Patent Pending
- Made in the USA



Frame Out™ Stem

FRAMED EXIT SIGN

TYPE
PROJECT

Ordering Format

PART NUMBER: FOE-S

Mounting Style	Letter Size	LED/Letter Color	Acrylic Style	Frame Out Finish
SMR = Stem Mount Round Canopy Adj. 1'-4' on site (included) SMS = Stem Mount Square Canopy Adj. 1'-4' on site (included) CL = Custom Lenth , add in notes (adder)	8 = 8 inch 6 = 6 inch	R = Red EXIT / 4 direction arrows included G = Green EXIT / 4 direction arrows included	FC1 = Clear - 1 side only FM1 = Mylar Mirror - 1 side only FM2 = Mylar Mirror - 2 side only	W = White B = Black SVR = Silver RAL = RAL Custom Color - enter RAL# in notes section PA = Plated Aluminum - enter plated finish in notes CW = Custom Wood Finish - see wood PN # enter in notes. AA = Anodized Aluminum - enter PN in notes section
J-Box Canopy Cover Finish	Battery	Voltage		
W = White Canopy /Stem B = Black Canopy/Stem	BB = 4.8 Volt NiCad 90Min./24hr Charge AC = AC only 2 watts no battery	V12 = Dual 120/277 Volt - AC 4 Watts		

NOTES

ORDER NUMBER:

Construction & Mounting

HOUSING

Housing is constructed of all extruded aluminum. The front cover is removable for easy installation.

MOUNTING

Stem mount comes with four, one foot stems that can be screwed together to drop exit one to four feet from the J-Box. Custom stems are also available.

LABELING

UL Approved IBEW Union Made


OPTICS

The "Frame Out" stem incorporates a strip of long-lasting LEDs at the bottom of the housing to illuminate the sign evenly. LEDs are red or green to enhance the red or green exit sign and direction arrows.

FINISH

Standard powder-coated colors are white, black and silver. Custom processed wood finishes, aluminum anodized finishes, chrome/gold plating, and custom finishes are available as well. We also accept RAL and Pantone numbers for powder-coating color choices.

Frame Out™ Stem



Electrical / Driver

- Drivers - Our drivers are specifically selected based on fixture application to ensure ultimate reliability and long life. We use only UL recognized brands of LED drivers. Our LED drivers feature HPF (high power factor), universal voltage 110 - 277 VAC and include 0-10V dimming. Please note, 277v has longer distances from power feed to power feed then 120v.
- UL 924 approved under emergency lighting and power equipment.
- EMR is a minimum of 90 minutes operation to meet code.
- Replace the battery with MYD battery PN AAA300, rated 300mah,4.8v.
- Our LED drivers feature HPF (high power factor), universal voltage 110 - 277 VAC.
- The emergency battery is a recyclable Ni-Cad battery at 4.8V @ 300ma.
- Test switch and charge indicator.
- Suitable for damp location. Use in 10 celsius (min) to 40 celsius (max) ambient temperature.

LED Performance

LED Output	CCT Color Temp	Watts	Lumens	Lumens per Watt	CCT Multiplier
Soft	Red	3.72 TW 120v	NA	NA	NA
Soft	Red	3.87 TW 277VAC	NA	NA	NA
Soft	Green	3.72 TW 120v	NA	NA	NA
Soft	Green	3.87 TW 277VAC	NA	NA	NA

- The table above is a quick reference.
- Our light engines are precisely designed for optimal operation of LED assemblies.
- Relamp LEDs with only factory lamp assembly.
- We design our own printed circuit boards to ensure high luminescence efficiency, low thermal resistance and long-term reliable operation.
- Light engines are easily replaced.

Certifications & Warranties

- Limited five-year (50,000 hours) warranty on all products. Limited ten-year (100,000 hours) warranty on all Lutron drivers.
- DLC listed products will have DLC Logo.
- Chicago Plenum and IC products are available upon request.
- Warranty does not cover damage caused by transport, damage caused by using the fixture in an area it is not UL rated for, damage caused by negligence, lack of maintenance, attempts to repair by unqualified or unauthorized personnel, by using non-original accessories/parts, fixtures installed in systems without power surge protection.
- UL and CUL listed for dry and damp locations.
- IBEW USA Union All fixtures are IBEW manufactured and assembled in the USA.
- We manufacture based on approved spec sheets and submittals signed by professionals responsible. Change orders must be in writing and will delay delivery.
- Picasso Lighting must receive in writing any thought to be defective products discovered, no later than 4 weeks from delivery to; ttoledo@picassoltg.com. Picasso Lighting will send a field technician to the site to evaluate the said defective product. We do accept field repair from licensed electrical contractors but not without a written agreement signed by Picasso Lighting official. Failure to adhere to all warranty and certifications will void any recompense and the warranty.



Note: Picasso lighting industries, LLC reserves the right to make any design changes which will not affect the overall appearance or performance of the product. All ceilings to be adequately reinforced by others. All fixtures to be wired by licensed electrician only. The information contained herein is the sole property of Picasso Lighting Industries, LLC and may not be used without prior written consent of Picasso Lighting Industries, LLC. The 'USGBC member logo' is a trademark owned by the U.S. Green building council and is used by permission. The logo signifies only that Picasso Lighting Industries, LLC is a USGBC member; USGBC does not review, certify, or endorse the products or services offered by its members.