

# MAX2.5 series LED Dropped Lens, Individual, Gypsum Ceiling-mounted



## INSTALLATION PROCEDURE (Sheet 1 of 2)


**DO NOT DISCARD**

**PLEASE READ CAREFULLY BEFORE BEGINNING INSTALLATION.**

Fixtures must be installed by licensed electricians in accordance with all local and national codes.

To prevent electrical shock, disconnect electrical supply before installing or servicing.


Before Beginning Installation, Locate the Following Components, Gather Required Tools:



### IMPORTANT NOTE:

Fixtures are shipped with "shipping braces" installed. To maintain proper fixture opening, brace must remain installed until fixture is properly


**(2) Persons Required to Complete Installation.**




Refer To Submittal Drawing Or Contact Factory For Actual Hole Locations

To Begin Installation, Provide Ceiling Opening and Blocking:

| Fixture O.A.L. | Ceiling Opening  |
|----------------|------------------|
| 24"            | 3 1/8" X 24 7/8" |
| 36"            | 3 1/8" X 36 7/8" |
| 48"            | 3 1/8" X 48 7/8" |
| 60"            | 3 1/8" X 60 7/8" |
| 72"            | 3 1/8" X 72 7/8" |
| 84"            | 3 1/8" X 84 7/8" |
| 96"            | 3 1/8" X 96 7/8" |



Blocking Must Be Adequately Secured To Support The Weight Of The Fixture(s).



Service Hotline: 1-201-246-8188  
Monday through Friday 9:00AM - 5:00PM









# MAX2.5 series LED Dropped Lens, Individual, Gypsum Ceiling-mounted



PICASSO LIGHTING

## INSTALLATION PROCEDURE (Sheet 2 of 2)



**POWER OFF**



Service Hotline: 1-201-246-8188  
Monday through Friday 9:00AM -  
5:00PM

**DO NOT DISCARD**  
**PLEASE READ CAREFULLY BEFORE**  
**BEGINNING INSTALLATION.**

### "EM" Battery Pack Activation



Installation and maintenance of the MAX2.5 luminaire may only be performed by qualified and licensed electricians in accordance with all applicable codes and standards.

Picasso Lighting Industries, LLC assumes no responsibility or liability for any unauthorized changes or modifications to the MAX2.5 luminaire.

The MAX2.5 luminaire is not intended for outdoor use.

Picasso Lighting Industries, LLC. shall assume no responsibility or liability for the integrity of the mounting surface and structure as well as the integrity of all components not provided by Picasso Lighting Industries, LLC.

Turn off line voltage and allow luminaire to completely cool before performing any maintenance including routine cleaning of luminaire.

Avoid touching LED light emitting surfaces while installing, replacing or providing maintenance to the luminaire.

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 10%.

Color temperature (k) is subject to a tolerance of +/- 150k from the nominal value.

Any component contained in this luminaire can only be replaced by the manufacturer or an agent thereof.

**Keep these INSTALLATION INSTRUCTIONS in a secure and readily accessible place for any future maintenance or for reference.**