



Picasso Lighting

IES INDOOR REPORT

PHOTOMETRIC FILENAME : BLD-4-PF-4-D5-I3-35-80-FW-W.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] 13313159.01
[TESTLAB] UL Verification Services Inc.
[ISSUE DATE] 10/29/2023JS
[MANUFAC] Picasso Lighting Industries
[LUMCAT] BLD-4-PF-4-D5-I3-35-80-FW-W
[LUMINAIRE] Formed White aluminum housing, plastic lens enclosures
[LAMP] 96 White LEDs down, 96 White LEDs up
[BALLAST] Two ERP PSB50W-1200-42-S Driver
[OTHER] 24.4 C, 119.989 V, 0.476329 A, 38.3 W, 0.974777 PF, 59.9705
[MORE] Hz
[OTHER] This test was performed using the calibrated photodetector met
[MORE] hod of absolute photometry.

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	3500
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	91
Total Luminaire Watts	38.3
Ballast Factor	1.00
CIE Type	General Diffuse
Spacing Criterion (0-180)	N.A.
Spacing Criterion (90-270)	N.A.
Spacing Criterion (Diagonal)	N.A.
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	4.00 ft
Luminous Width (90-270)	0.13 ft
Luminous Height	0.33 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	12867	4702	3773
55	11935	3516	2765
65	10678	2430	1888
75	8787	1424	1098
85	5260	522	433

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BLD-4-PF-4-D5-I3-35-80-FW-W.IES

CANDELA TABULATION

	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>
0.0	704.93	704.93	704.93	704.93	704.93
0.5	704.14	705.63	702.83	704.14	709.46
1.0	704.06	705.54	702.75	704.14	709.29
1.5	703.88	705.45	702.57	703.97	709.03
2.0	703.53	705.19	702.49	703.79	708.59
2.5	703.27	704.84	702.22	703.45	708.16
3.0	702.83	704.40	701.96	703.10	707.46
3.5	702.22	703.97	701.61	702.66	706.76
4.0	701.70	703.45	701.18	702.14	706.06
4.5	701.09	702.92	700.65	701.61	705.36
5.0	700.48	702.31	700.04	700.92	704.67
5.5	699.78	701.61	699.35	700.22	703.88
6.0	699.00	700.83	698.47	699.43	703.10
6.5	698.30	700.04	697.60	698.56	702.14
7.0	697.17	699.17	696.64	697.69	701.18
7.5	696.12	698.12	695.51	696.55	700.22
8.0	695.16	697.08	694.29	695.51	699.00
8.5	694.11	695.94	693.15	694.37	697.78
9.0	692.89	694.64	691.84	693.15	696.38
9.5	691.67	693.33	690.45	691.76	694.90
10.0	690.27	692.02	689.05	690.27	693.24
10.5	688.88	690.54	687.66	688.62	691.58
11.0	687.40	688.88	686.18	686.96	689.58
11.5	685.91	687.40	684.61	685.22	687.75
12.0	684.26	685.74	682.95	683.38	685.74
12.5	682.69	684.08	681.38	681.47	683.73
13.0	680.85	682.34	679.55	679.46	681.64
13.5	679.11	680.59	677.71	677.45	679.46
14.0	677.19	678.76	675.88	675.36	677.37
14.5	675.27	676.84	673.88	673.18	675.10
15.0	673.27	674.84	671.87	671.00	672.92
15.5	671.35	672.83	669.78	668.73	670.74
16.0	669.17	670.74	667.60	666.46	668.47
16.5	667.07	668.64	665.42	664.11	666.20
17.0	664.81	666.46	663.06	661.75	663.85
17.5	662.54	664.11	660.71	659.31	661.40
18.0	660.27	661.75	658.26	656.69	658.87
18.5	657.83	659.31	655.73	654.16	656.35
19.0	655.47	656.78	653.12	651.46	653.73
19.5	652.94	654.16	650.59	648.67	651.20
20.0	650.33	651.46	647.80	645.88	648.41
20.5	647.62	648.76	645.01	643.00	645.70
21.0	645.01	645.97	642.13	640.21	643.00
21.5	642.30	643.09	639.34	637.24	640.12
22.0	639.51	640.21	636.28	634.28	637.16
22.5	636.55	637.16	633.23	631.31	634.10
23.0	633.75	634.19	630.09	628.26	630.79
23.5	630.79	631.14	627.04	625.21	627.56
24.0	627.82	628.00	623.81	621.98	624.42
24.5	624.68	624.86	620.50	618.75	621.19
25.0	621.54	621.72	617.18	615.53	617.88
25.5	618.32	618.49	613.96	612.21	614.65
26.0	615.09	615.00	610.47	608.90	611.16
26.5	611.77	611.69	607.06	605.49	607.76

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BLD-4-PF-4-D5-I3-35-80-FW-W.IES

CANDELA TABULATION - (Cont.)

27.0	608.37	608.20	603.58	601.83	604.19
27.5	604.97	604.71	600.09	598.34	600.70
28.0	601.48	601.05	596.60	594.68	597.21
28.5	597.82	597.38	593.02	591.10	593.46
29.0	594.16	593.72	589.36	587.35	589.80
29.5	590.67	589.97	585.70	583.60	586.13
30.0	586.92	586.22	582.03	579.85	582.47
30.5	583.34	582.29	578.37	576.01	578.72
31.0	579.68	578.37	574.62	572.26	574.71
31.5	575.93	574.44	570.78	568.43	570.78
32.0	572.26	570.52	567.03	564.41	566.86
32.5	568.34	566.51	563.11	560.49	563.11
33.0	564.50	562.41	559.18	556.48	559.18
33.5	560.58	558.40	555.26	552.64	555.17
34.0	556.56	554.21	551.33	548.63	551.07
34.5	552.55	550.02	547.23	544.61	546.97
35.0	548.45	545.92	543.13	540.43	543.04
35.5	544.35	541.74	539.21	536.24	539.12
36.0	540.17	537.46	535.11	532.05	535.02
36.5	535.98	533.19	530.92	527.87	530.92
37.0	531.62	529.00	526.73	523.59	526.73
37.5	527.26	524.64	522.46	519.32	522.46
38.0	522.90	520.28	518.19	515.13	518.36
38.5	518.53	515.83	513.91	510.95	514.00
39.0	514.00	511.38	509.55	506.67	509.38
39.5	509.64	506.76	505.19	502.31	504.93
40.0	505.02	502.31	501.00	497.86	500.57
40.5	500.48	497.69	496.55	493.50	495.94
41.0	495.77	493.07	492.11	488.97	491.58
41.5	491.15	488.53	487.57	484.52	486.96
42.0	486.61	483.73	483.04	479.98	482.51
42.5	481.99	479.11	478.41	475.45	477.89
43.0	477.28	474.40	473.88	470.82	473.27
43.5	472.48	469.69	469.17	466.20	468.64
44.0	467.86	464.89	464.54	461.49	464.11
44.5	463.06	460.10	459.75	456.78	459.40
45.0	458.26	455.30	454.86	452.16	454.51
45.5	453.38	450.50	450.07	447.45	449.72
46.0	448.50	445.70	445.09	442.56	444.92
46.5	443.61	440.73	440.30	437.77	439.95
47.0	438.64	435.76	435.41	432.88	434.98
47.5	433.58	430.88	430.44	428.00	430.09
48.0	428.61	425.99	425.47	423.20	424.86
48.5	423.46	420.93	420.58	418.40	419.89
49.0	418.40	415.96	415.53	413.52	414.74
49.5	413.34	410.90	410.55	408.55	409.86
50.0	408.29	405.67	405.49	403.58	404.88
50.5	403.05	400.61	400.52	398.60	400.00
51.0	397.82	395.55	395.46	393.55	395.03
51.5	392.67	390.41	390.41	388.57	390.06
52.0	387.44	385.35	385.35	383.52	385.00
52.5	382.29	380.11	380.20	378.37	379.94
53.0	377.15	374.97	374.97	373.31	374.79
53.5	371.91	369.91	369.73	368.08	369.65
54.0	366.59	364.68	364.50	362.93	364.68
54.5	361.45	359.53	359.18	357.78	359.53

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BLD-4-PF-4-D5-I3-35-80-FW-W.IES

CANDELA TABULATION - (Cont.)

55.0	356.13	354.30	353.86	352.64	354.30
55.5	350.72	349.06	348.63	347.49	348.98
56.0	345.31	343.83	343.31	342.26	343.65
56.5	339.73	338.60	337.90	337.11	338.25
57.0	334.23	333.28	332.49	331.88	333.01
57.5	328.74	327.95	327.08	326.73	327.61
58.0	323.24	322.46	321.76	321.50	322.37
58.5	317.84	316.96	316.44	316.27	317.14
59.0	312.34	311.47	311.03	311.12	311.82
59.5	306.93	306.15	305.63	305.89	306.41
60.0	301.44	300.74	300.22	300.57	301.18
60.5	296.12	295.16	294.81	295.33	295.94
61.0	290.80	289.75	289.40	290.01	290.71
61.5	285.39	284.26	284.17	284.78	285.48
62.0	279.90	278.85	278.76	279.46	280.16
62.5	274.49	273.44	273.44	274.14	275.01
63.0	269.08	268.03	268.12	268.82	269.86
63.5	263.58	262.63	262.80	263.58	264.72
64.0	258.26	257.22	257.48	258.26	259.49
64.5	252.77	251.90	252.07	253.03	254.25
65.0	247.27	246.49	246.66	247.71	249.02
65.5	241.78	241.08	241.34	242.48	243.79
66.0	236.28	235.67	235.94	237.24	238.55
66.5	230.70	230.27	230.61	232.01	233.23
67.0	225.12	224.77	225.38	226.78	227.91
67.5	219.62	219.28	220.06	221.46	222.59
68.0	213.87	213.87	214.65	216.22	217.27
68.5	208.37	208.29	209.25	210.99	211.95
69.0	202.70	202.88	203.92	205.67	206.54
69.5	197.03	197.30	198.60	200.44	201.05
70.0	191.45	191.89	193.20	195.03	195.29
70.5	185.96	186.66	188.14	189.80	189.71
71.0	180.29	181.16	182.90	184.82	184.74
71.5	174.79	175.93	177.85	179.42	179.50
72.0	170.00	170.52	172.61	174.10	174.36
72.5	164.50	165.02	167.38	168.86	169.21
73.0	159.18	159.70	162.15	163.63	164.15
73.5	153.77	154.38	157.00	158.40	159.27
74.0	148.98	149.06	151.68	153.16	154.38
74.5	143.83	144.27	146.45	148.19	149.50
75.0	138.60	139.12	141.39	143.31	144.61
75.5	133.54	134.23	136.33	138.42	139.82
76.0	128.39	129.18	131.53	133.97	135.54
76.5	123.33	124.12	126.56	129.35	130.75
77.0	118.27	119.06	121.59	124.55	125.77
77.5	113.30	114.00	116.79	119.84	120.80
78.0	108.24	109.03	112.08	114.96	115.83
78.5	103.18	104.06	107.37	110.16	110.95
79.0	98.30	99.17	102.66	105.28	105.97
79.5	93.33	94.29	97.86	100.48	101.18
80.0	88.44	89.32	93.07	95.77	96.38
80.5	83.65	84.34	88.36	91.15	91.84
81.0	78.85	79.46	83.56	86.61	87.31
81.5	74.05	74.66	78.94	82.16	82.95
82.0	69.43	69.95	74.23	77.80	78.76
82.5	64.72	65.33	69.60	73.53	74.57

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BLD-4-PF-4-D5-I3-35-80-FW-W.IES

CANDELA TABULATION - (Cont.)

83.0	60.10	60.88	65.24	69.43	70.48
83.5	55.56	56.52	60.88	65.42	66.46
84.0	50.94	51.98	56.87	61.49	62.54
84.5	46.49	47.54	52.94	57.65	58.79
85.0	41.60	43.26	49.11	53.99	55.12
85.5	37.16	38.99	45.44	50.50	51.64
86.0	32.71	34.89	41.87	47.10	48.41
86.5	28.61	30.96	38.55	44.13	45.53
87.0	24.60	27.13	34.80	40.56	41.87
87.5	20.24	23.55	31.57	36.46	36.98
88.0	15.79	20.76	29.04	34.80	35.50
88.5	11.51	18.67	28.52	34.63	35.24
89.0	8.55	17.79	29.13	35.50	35.85
89.5	6.37	17.44	30.35	36.63	36.81
90.0	4.54	17.62	31.84	38.12	38.20
90.5	1.18	1.47	1.47	1.77	1.87
91.0	2.65	1.38	1.47	1.96	1.96
91.5	3.93	1.47	1.47	1.96	1.96
92.0	5.30	1.87	1.47	1.77	1.96
92.5	6.78	2.26	1.57	2.06	1.96
93.0	8.25	2.85	1.96	2.06	1.96
93.5	9.92	3.34	2.16	2.26	2.16
94.0	11.69	4.03	2.55	2.46	2.36
94.5	13.36	4.72	2.75	2.65	2.55
95.0	15.42	5.50	3.05	2.95	2.85
95.5	17.68	6.29	3.44	3.14	3.05
96.0	19.94	6.88	3.93	3.44	3.34
96.5	22.50	7.47	4.32	3.73	3.63
97.0	24.85	8.06	5.01	3.93	3.93
97.5	27.41	8.55	5.60	4.22	4.22
98.0	30.06	9.23	6.09	4.62	4.62
98.5	33.01	10.22	6.68	5.11	5.01
99.0	35.85	11.69	7.07	5.70	5.60
99.5	38.70	13.36	7.66	6.39	6.19
100.0	41.55	15.91	8.15	6.97	6.68
100.5	44.60	18.96	8.55	7.76	7.37
101.0	47.45	22.59	8.94	8.45	8.06
101.5	50.59	27.41	9.33	9.04	8.64
102.0	53.83	33.20	9.53	9.63	9.33
102.5	56.78	39.49	9.72	10.22	9.82
103.0	59.92	46.56	10.02	10.71	10.31
103.5	62.97	53.83	10.41	11.20	10.81
104.0	65.91	61.79	11.00	11.59	11.20
104.5	68.96	70.43	11.79	11.89	11.49
105.0	72.00	80.45	13.06	12.08	11.79
105.5	75.05	93.12	14.54	12.28	11.98
106.0	78.19	105.21	16.31	12.57	12.18
106.5	81.34	114.24	18.76	12.77	12.18
107.0	84.28	121.12	21.51	12.97	12.38
107.5	87.33	127.80	24.95	13.26	12.48
108.0	90.28	133.99	28.78	13.65	12.67
108.5	93.32	139.39	33.20	14.24	12.87
109.0	96.27	144.50	38.90	15.13	13.16
109.5	99.21	149.12	45.97	16.01	13.65
110.0	102.36	153.63	55.01	17.19	14.34
110.5	105.30	157.86	65.32	18.66	15.13

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BLD-4-PF-4-D5-I3-35-80-FW-W.IES

CANDELA TABULATION - (Cont.)

111.0	108.35	161.89	76.92	20.53	16.21
111.5	111.30	165.72	89.10	22.79	17.19
112.0	114.24	169.45	102.36	25.44	18.57
112.5	117.29	173.18	116.11	28.49	20.14
113.0	120.04	176.72	130.35	32.02	22.30
113.5	122.99	180.45	146.76	36.15	24.46
114.0	125.93	183.89	164.24	41.16	27.21
114.5	128.68	187.43	183.89	47.74	30.45
115.0	131.43	190.77	203.34	55.89	33.99
115.5	134.28	194.20	223.87	66.60	38.21
116.0	137.13	197.35	244.50	78.19	43.61
116.5	139.98	200.49	266.90	91.45	50.49
117.0	142.83	203.54	290.37	105.89	59.14
117.5	145.58	206.58	312.67	121.22	69.55
118.0	148.33	209.43	332.51	138.02	81.63
118.5	151.18	212.38	347.84	155.60	94.79
119.0	154.03	215.32	361.39	174.75	109.63
119.5	156.78	218.07	373.38	195.48	125.15
120.0	159.53	220.92	384.87	219.06	142.24
120.5	162.28	223.67	395.19	244.01	160.12
121.0	165.03	226.52	404.03	271.02	179.76
121.5	167.78	229.17	411.20	298.43	201.28
122.0	170.53	231.73	417.49	326.92	224.56
122.5	173.18	234.48	422.99	356.78	250.79
123.0	175.93	236.94	427.80	386.94	278.78
123.5	178.78	239.49	432.12	419.74	307.96
124.0	181.34	241.85	435.76	451.77	338.11
124.5	184.09	244.40	439.39	480.55	369.35
125.0	186.64	246.86	442.34	504.81	401.57
125.5	189.29	249.21	445.38	525.44	436.84
126.0	191.85	251.47	447.94	543.32	471.22
126.5	194.40	253.83	450.39	559.33	502.65
127.0	197.05	256.29	452.75	575.05	531.43
127.5	199.71	258.55	455.01	588.70	554.91
128.0	202.36	260.90	457.37	599.90	576.03
128.5	204.72	263.26	459.23	608.74	594.89
129.0	207.27	265.52	461.10	616.40	612.38
129.5	209.72	267.68	462.77	622.59	628.29
130.0	212.28	269.84	464.44	627.80	641.75
130.5	214.64	272.00	466.01	631.83	652.46
131.0	217.09	274.17	467.49	635.36	660.90
131.5	219.65	276.33	468.86	638.21	668.07
132.0	221.91	278.29	470.14	640.57	674.07
132.5	224.36	280.45	471.02	642.63	678.98
133.0	226.72	282.51	472.00	644.30	682.91
133.5	229.17	284.48	472.89	645.48	686.25
134.0	231.53	286.44	473.38	646.46	689.00
134.5	233.89	288.41	473.97	647.25	691.45
135.0	236.15	290.37	474.36	647.84	693.32
135.5	238.51	292.24	474.36	648.33	694.70
136.0	240.86	294.20	474.56	648.53	695.87
136.5	243.12	295.97	474.66	648.43	696.66
137.0	245.38	297.74	474.36	647.84	697.05
137.5	247.64	299.51	474.07	647.05	697.45
138.0	249.90	301.38	473.67	645.97	697.35
138.5	252.06	303.05	472.99	644.79	696.76

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BLD-4-PF-4-D5-I3-35-80-FW-W.IES

CANDELA TABULATION - (Cont.)

139.0	254.32	304.81	472.20	643.32	695.87
139.5	256.39	306.39	471.51	641.85	694.70
140.0	258.55	308.06	470.63	640.08	693.12
140.5	260.71	309.63	469.35	638.11	691.16
141.0	262.77	311.20	468.17	635.76	689.00
141.5	264.93	312.77	466.99	633.01	686.44
142.0	266.99	314.24	465.72	629.96	683.99
142.5	269.25	315.82	464.34	626.52	680.94
143.0	271.12	317.29	462.97	623.08	677.70
143.5	273.28	318.66	461.49	619.25	674.07
144.0	275.44	320.04	459.92	615.42	670.14
144.5	277.31	321.41	458.45	611.39	665.82
145.0	279.27	322.79	456.78	606.97	661.20
145.5	281.24	324.07	455.21	602.55	656.29
146.0	283.10	325.44	453.34	597.84	651.18
146.5	285.07	326.72	451.57	593.22	645.97
147.0	287.03	327.80	449.80	588.21	640.47
147.5	289.10	328.98	448.04	583.20	634.77
148.0	290.86	329.96	446.17	578.00	628.68
148.5	292.63	331.04	444.30	572.89	622.79
149.0	294.50	332.02	442.34	567.78	616.70
149.5	296.27	333.01	440.47	562.48	610.41
150.0	297.84	333.89	438.51	557.17	604.03
150.5	299.61	334.68	436.44	551.87	597.54
151.0	301.18	335.46	434.38	546.56	591.06
151.5	302.85	336.25	432.22	541.16	584.48
152.0	304.32	337.03	430.26	535.85	578.00
152.5	305.89	337.82	428.09	530.35	571.41
153.0	307.47	338.41	426.03	525.05	564.93
153.5	308.84	339.10	423.97	519.84	558.45
154.0	310.41	339.59	421.81	514.44	551.77
154.5	311.69	340.08	419.65	509.14	545.28
155.0	313.06	340.67	417.49	503.93	538.61
155.5	314.54	341.16	415.32	498.62	532.12
156.0	315.91	341.75	413.26	493.32	525.54
156.5	317.19	342.24	411.10	488.21	519.16
157.0	318.47	342.63	408.94	482.91	512.77
157.5	319.74	343.03	406.68	477.90	506.39
158.0	320.83	343.32	404.72	472.89	500.20
158.5	322.10	343.61	402.55	467.78	494.11
159.0	323.28	343.81	400.39	462.87	487.92
159.5	324.36	344.01	398.23	457.96	481.93
160.0	325.44	344.30	396.17	453.24	475.93
160.5	326.52	344.50	394.01	448.43	469.94
161.0	327.50	344.70	391.94	443.81	464.24
161.5	328.49	344.99	389.88	439.19	458.45
162.0	329.47	345.09	387.92	434.77	452.85
162.5	330.45	345.28	385.85	430.35	447.45
163.0	331.34	345.38	383.89	425.93	441.94
163.5	332.22	345.48	382.12	421.81	436.74
164.0	333.10	345.48	380.26	417.58	431.53
164.5	333.89	345.58	378.39	413.56	426.62
165.0	334.68	345.68	376.62	409.53	421.71
165.5	335.56	345.68	374.85	405.80	416.99
166.0	336.35	345.68	373.08	401.96	412.48
166.5	337.03	345.78	371.51	398.43	407.96

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BLD-4-PF-4-D5-I3-35-80-FW-W.IES

CANDELA TABULATION - (Cont.)

167.0	337.72	345.78	369.84	394.99	403.83
167.5	338.31	345.68	368.27	391.55	399.61
168.0	339.00	345.68	366.70	388.31	395.68
168.5	339.59	345.58	365.13	385.17	391.75
169.0	340.28	345.68	363.65	382.22	388.21
169.5	340.86	345.68	362.18	379.17	384.48
170.0	341.36	345.68	360.90	376.42	381.24
170.5	342.04	345.68	359.53	373.67	378.00
171.0	342.53	345.68	358.25	371.12	374.85
171.5	342.93	345.68	357.07	368.66	372.00
172.0	343.52	345.68	355.89	366.31	368.96
172.5	343.91	345.68	354.81	364.24	366.60
173.0	344.30	345.68	353.63	362.28	364.05
173.5	344.60	345.68	352.75	360.31	361.79
174.0	344.99	345.68	351.77	358.64	359.53
174.5	345.38	345.68	350.98	357.17	357.56
175.0	345.58	345.58	350.10	355.70	355.70
175.5	345.87	345.58	349.61	354.42	354.22
176.0	346.07	345.48	349.02	353.34	352.65
176.5	346.37	345.58	348.43	352.26	351.47
177.0	346.46	345.48	348.13	351.38	350.39
177.5	346.66	345.48	347.64	350.49	349.41
178.0	346.76	345.48	347.35	349.61	348.72
178.5	346.86	345.48	347.05	348.82	348.23
179.0	346.95	345.38	346.76	348.23	347.84
179.5	346.95	345.38	346.46	347.84	347.54
180.0	346.66	346.66	346.66	346.66	346.66

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BLD-4-PF-4-D5-I3-35-80-FW-W.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	256.39	N.A.	7.30
0-30	541.34	N.A.	15.50
0-40	881.54	N.A.	25.20
0-60	1548.51	N.A.	44.20
0-80	1943.02	N.A.	55.50
0-90	1999.19	N.A.	57.10
10-90	1932.56	N.A.	55.20
20-40	625.15	N.A.	17.90
20-50	975.79	N.A.	27.90
40-70	911.62	N.A.	26.00
60-80	394.51	N.A.	11.30
70-80	149.86	N.A.	4.30
80-90	56.17	N.A.	1.60
90-110	48.00	N.A.	1.40
90-120	188.50	N.A.	5.40
90-130	511.17	N.A.	14.60
90-150	1163.17	N.A.	33.20
90-180	1500.76	N.A.	42.90
110-180	1452.76	N.A.	41.50
0-180	3499.95	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	66.62
10-20	189.77
20-30	284.95
30-40	340.20
40-50	350.64
50-60	316.33
60-70	244.65
70-80	149.86
80-90	56.17
90-100	7.07
100-110	40.93
110-120	140.49
120-130	322.67
130-140	361.03
140-150	290.97
150-160	195.98
160-170	107.81
170-180	33.80


IES INDOOR REPORT
PHOTOMETRIC FILENAME : BLD-4-PF-4-D5-I3-35-80-FW-W.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	109	109	109	109	101	101	101	101	87	87	87	74	74	74	63	63	63	57
1	99	94	90	87	92	88	84	81	76	73	71	65	63	61	55	53	52	47
2	90	82	76	70	83	77	71	66	66	62	58	57	54	51	48	46	44	39
3	82	72	64	58	76	67	61	55	58	53	49	50	46	43	42	39	37	33
4	75	64	55	49	69	60	52	47	52	46	41	44	40	36	38	34	32	28
5	69	57	48	42	64	53	46	40	46	40	36	40	35	31	34	30	27	24
6	63	51	42	37	59	48	40	35	42	36	31	36	31	28	31	27	24	21
7	58	46	38	32	54	43	36	30	38	32	27	33	28	24	28	24	21	19
8	54	42	34	28	50	39	32	27	34	28	24	30	25	22	26	22	19	17
9	51	38	30	25	47	36	29	24	31	26	22	27	23	19	24	20	17	15
10	47	35	28	23	44	33	26	22	29	23	20	25	21	18	22	18	16	14

POLAR GRAPH



Maximum Candela = 709.46 Located At Horizontal Angle = 90, Vertical Angle = .5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (.5) (Through Max. Cd.)
3 - Horizontal Cone Through Vertical Angle (2)
4 - Horizontal Cone Through Vertical Angle (90)