

Cove - 100

COVE

TYPE
PROJECT

Overview

- Same as Cove 200 but lower lumen output.
- 2 ft., 3 ft., 4 ft., 6 ft., and 8 ft.
- Tool-less snap-on gear tray
- Die formed 20GA steel housing
- Quick connect wiring system available
- Integral 0-10V dimming driver standard
- 120° spread standard



Cove - 100

COVE

TYPE
PROJECT

Ordering Format

PART NUMBER: CV1-CF

Size	Lumens Indirect	CCT Available	CRI Available	Optics
2 = 2 Feet	I3 = 350 LPF	27 = 2700 Kelvins	80 = 80-85 CRI	CL = Clear Lens
3 = 3 Feet	I5 = 500 LPF	30 = 3000 Kelvins	90 = 90-95 CRI	
4 = 4 Feet	I7 = 750 LPF	35 = 3500 Kelvins		
6 = 6 Feet	I10 = 1000 LPF	40 = 4000 Kelvins		
CL = Custom Length, add in notes	I20 = I20=2200 LPF	TW = Tunable White 2700-5000 Kelvins		
8 = 8 Feet				
Mounting	Driver / Voltage	Fixture Finish	Options	
SM = Surface Mount	ND 1 = Non-Dim Universal 120VAC ND 2 = Non-Dim Universal 277VAC ZT 1 = 0-10v dimming 120v dual 1% ZT 2 = 0-10v dimming 277v dual 1% CC = Custom Control - Add in notes LE1 = Lutron EcoSystem 1% DLC EE CCR / PWM SoftOnFadeToBlack LE5 = Lutron EcoSystem 5% DLC EE CCR	W = Standard White	EMD = Emergency Driver - Battery Backup 120-277VAC 3ft. Min. IW = Inverter Wiring	

NOTES

ORDER NUMBER:

Cove - 100

COVE

TYPE
PROJECT

Construction & Mounting

HOUSING

Housing is extruded aluminum and can be installed first, 1/2" knockout for power is supplied on sides and bottom. Quick connects are supplied for easy contractor installation.

REFLECTOR

Integral powder-coated LED housing with clear dust lens for full light output.

FINISH



Standard powder-coated colors are white. Fixtures are not limited to white, consult factory for special applications.

OPTICS

LED channel is provided with an integral clear dust lens.

MOUNTING

Fixtures have pre-drilled holes for 1/4" screws. Cove mounted fixtures have 1/2" knockout for power feed.



Electrical / Driver

- Drivers - Our drivers are specifically selected based on fixture application to ensure ultimate reliability and long life. We use only UL recognized brands of LED drivers. Our LED drivers feature HPF (high power factor), universal voltage 110 - 277 VAC and include 0-10V dimming. Please note, 277v has longer distances from power feed to power feed then 120v.
- If required, we can supply premium drivers such as Lutron, Eldoled and others upon request. Advanced control systems compliant drivers such as POE,DALI, DMX, etc. are also available, please consult factory.
- Rated life (90% survivorship) of 50,000 hours at 50° C max. ambient (and 70° C max. case) temperature. At maximum driver load: Efficiency >84%, PF>0.9, THD
- POE - We are working with Molex/Igor POE systems. We can add a POE driver into our fixtures or remote them. Based on the fixture you select, we will notify you (or you can contact the factory) to see if we can install the P-driver or the P-driver needs to be remote. Just add POE1 in the spec and we will advise. Please keep in mind you need to specify a complete POE control system before specifying POE1.
- Our LED drivers feature HPF (high power factor), universal voltage 110 - 277 VAC and include 0-10V dimming.
- Emergency drivers are factory installed as an option, long life, high temperature, recyclable Ni-Cad battery pack with test switch and charge indicator. EMR is minimum of 90 minutes operation to meet code.
- Whip - Six feet long, wiring RHOS/Reach Compliant, 18 gauge, 600v rated, Specify wired to the fixture as an OPTION.

LED Performance

LED Output	CCT Color Temp	Watts	Lumens	Lumens per Watt	CCT Multiplier
Low (indirect)	3000	2.98 WPF	350 LPF	119 LPW	2700 = .95
Medium (indirect)	3000	4.3 WPF	500 LPF	117 LPW	3000 = 1
High (indirect)	3000	6.55 WPF	750 LPF	115 LPW	3500 = 1.01
Very High (indirect)	3000	8.8 WPF	1000 LPF	114 LPW	4000 = 1.03
Super High	3000	20 WPF	2200 LPF	110 LPW	See Above

- The table above is a quick reference. When calculating loads make sure you add direct and indirect LPW to get total wattage. Please refer to photometric report for detailed information.
- Our light engines are precisely designed for optimal operation of LED assemblies.
- Our standard LED's CCT (correlated color temperature) range is 2700K to 4000K. Other CCT values are available upon request.
- We log LED bin codes for each project we supply to ensure color consistency and keep a record of those projects for future reference.
- CRI offered is 80+, and 90+ Note: on 90+ CRI use .85 multiplier
- Tunable white, warm dim and other special LED colors available.
- We design our own printed circuit boards to ensure high luminescence efficiency, low thermal resistance and long-term reliable operation.
- Light engines are easily replaced.
- We use only recognized brand LED's with 3 SDCM (standard deviation color matching) with high color consistency. 2 SDCM available upon request.
- LRP - "LED Reel Program" – LED's for printed circuit boards come on reels' like old 8mm projectors and they're sold in lots just like fabric. At Picasso Lighting, we have a program where we make sure all of your reels come from the same lot for each project. This ensures excellent color consistency in large open spaces.
- LED life is rated at 50,000 hours
- Custom Lumens Available

Certifications & Warranties

Cove - 100

COVE

TYPE PROJECT

- Limited five-year (50,000 hours) warranty on all products. Limited ten-year (100,000 hours) warranty on all Lutron drivers.
- DLC listed products will have DLC Logo.
- Chicago Plenum and IC products are available upon request.
- Warranty does not cover damage caused by transport, damage caused by using the fixture in an area it is not UL rated for, damage caused by negligence, lack of maintenance, attempts to repair by unqualified or unauthorized personnel, by using non-original accessories/parts, fixtures installed in systems without power surge protection.
- UL and CUL listed for dry and damp locations.
- IBEW USA Union All fixtures are IBEW manufactured and assembled in the USA.
- We manufacture based on approved spec sheets and submittals signed by professionals responsible. Change orders must be in writing and will delay delivery.
- Picasso Lighting must receive in writing any thought to be defective products discovered, no later than 4 weeks from delivery to; ttoledo@picassoltg.com. Picasso Lighting will send a field technician to the site to evaluate the said defective product. We do accept field repair from licensed electrical contractors but not without a written agreement signed by Picasso Lighting official. Failure to adhere to all warranty and certifications will void any recompense and the warranty.



Note: Picasso lighting industries, LLC reserves the right to make any design changes which will not affect the overall appearance or performance of the product. All ceilings to be adequately reinforced by others. All fixtures to be wired by licensed electrician only. The information contained herein is the sole property of Picasso Lighting Industries, LLC and may not be used without prior written consent of Picasso Lighting Industries, LLC. The 'USGBC member logo' is a trademark owned by the U.S. Green building council and is used by permission. The logo signifies only that Picasso Lighting Industries, LLC is a USGBC member; USGBC does not review, certify, or endorse the products or services offered by its members.