

# Emily EZ-P Continuous

EZ SHIP

TYPE  
PROJECT

## Overview

- EZ Ship Emily is when your looking for a fast solution to a space where you need an 8 foot or 4 foot continuous row up to 48 feet with one power supply.
- No waiting for Submittals, Drawings, Bill of Materials, or Approvals.
- Just order from the cut sheet.
- Aesthetically pleasing Emily has a round design with a tool-less snap on gear tray and a snap on frosted acrylic lens. End caps are milled for eliminating light leaks.
- Direct lighting only.
- If you need this product as an individual, look under EZ individual.
- If you need this product in special lengths, colors, and patterns, please look at our standard Emily under pendants large.



# Emily EZ-P Continuous

EZ SHIP

TYPE  
PROJECT

## Ordering Format

PART NUMBER: EZ-EMI-PDC

Size	Lumens Direct	CCT Available	CRI Available	Optics
4 = 4 Feet	D3 = 350 LPF	30 = 3000 Kevlins	90 = 90-95 CRI	FW = Frosted White
8 = 8 Feet	D5 = 500 LPF D7 = 750 LPF	35 = 3500 Kelvins		
Mounting	Driver / Voltage	Fixture Finish	Canopy/Power Cord Color	Options
JRW = Round White 5in Canopy J-Box - Joiner Kit White  JRB = Round White 5in Canopy J-Box - Joiner Kit Black	ZTU = Universal 0-10v dimming 120v/277v dual 1%	W = Standard White BK = Standard White	CWPW-R-W = Round Canopy White/Power Cord White W/Start Feed/ End Run Kit in White  CWPW-R-B = Round Canopy White/Power Cord White W/Start Feed/ End Run Kit in Black	EMD = Emergency Driver - Battery Backup 120-277VAC

### NOTES

**ORDER NUMBER:**

## Construction & Mounting

### HOUSING

Extruded aluminum housings are supplied in nominal lengths of 4 or 8 feet End caps and joiners are extruded, milled aluminum and encapsulate ends of lenses to minimize light leaks.

### REFLECTOR

Integral powder-coated LED housing with excessive reflectivity for increased lumen output

### FINISH

Standard powder-coated colors EZ Ship are white, black

### OPTICS

Extruded round snap-in frosted acrylic lens formulated for LED light sources

### MOUNTING

Cable mounting with various 5" canopies and power feeds. canopy color and cord will be white or black. Cable uses gripper style locking for field adjustments, 48" standard. Canopy mounts to standard J-box.

**Emily EZ Ship  
Dropped Lens Pendant  
Continuous Fixture**

**A = Power / End Cap Kit**  
**B = Joiner Hanging Point**  
**C = Universal 4' or 8' Fixture**

EXAMPLE	Description	Qty.
A	Power/End Cap Kit (Start of Run and End of Run Kit)	1
B	Joiner (Hanging Point)	1
C	8' Fixture Continuous	2

# Emily EZ-P Continuous

EZ SHIP

TYPE

PROJECT



## Electrical / Driver

- Drivers - Our drivers are specifically selected based on fixture application to ensure ultimate reliability and long life. We use only UL recognized brands of LED drivers. Our LED drivers feature HPF (high power factor), universal voltage 110 - 277 VAC and include 0-10V dimming. Please note, 277v has longer distances from power feed to power feed than 120v.
- If required, we can supply premium drivers such as Lutron, Eldoled and others upon request. Advanced control systems compliant drivers such as POE, DALI, DMX, etc. are also available, please consult factory.
- Rated life (90% survivorship) of 50,000 hours at 50° C max. ambient (and 70° C max. case) temperature. At maximum driver load: Efficiency >84%, PF>0.9, THD
- Our LED drivers feature HPF (high power factor), universal voltage 110 - 277 VAC and include 0-10V dimming.
- Emergency drivers are factory installed as an option, long life, high temperature, recyclable Ni-Cad battery pack with test switch and charge indicator. EMR is minimum of 90 minutes operation to meet code.
- POE - We are working with Molex/Igor POE systems. We can add a POE driver into our fixtures or remote them. Based on the fixture you select, we will notify you (or you can contact the factory) to see if we can install the P-driver or the P-driver needs to be remote. Just add POE1 in the spec and we will advise. Please keep in mind you need to specify a complete POE control system before specifying POE1.

## LED Performance

LED Output	CCT Color Temp	Watts	Lumens	Lumens per Watt	CCT Multiplier
Low	3000	4 WPF	350 LPF	89 LPW	90+ CRI
Medium	3000	5.7 WPF	500 LPF	88 LPW	90+ CRI
High	3000	8.5 WPF	750 LPF	88 LPW	90+ CRI
Low	3500	3.9 WPF	350 LPF	90 LPW	90+ CRI
Medium	3500	5.5 WPF	500 LPF	90 LPW	90+ CRI
High	3500	8.5 WPF	750 LPF	90 LPW	90+ CRI

- The table above is a quick reference based on per foot. Please refer to photometric report for detailed information.
- Our light engines are precisely designed for optimal operation of LED assemblies.
- Our standard LED's CCT (correlated color temperature) range is 2700K to 4000K. Other CCT values are available upon request.
- We log LED bin codes for each project we supply to ensure color consistency and keep a record of those projects for future reference.
- CRI offered is 80+, and 90+ Note: on 90+ CRI use .85 multiplier
- We design our own printed circuit boards to ensure high luminescence efficiency, low thermal resistance and long-term reliable operation.
- Light engines are easily replaced.
- We use only recognized brand LED's with 3 SDCM (standard deviation color matching) with high color consistency. 2 SDCM available upon request.
- LRP - "LED Reel Program" – LED's for printed circuit boards come on reels' like old 8mm projectors and they're sold in lots just like fabric. At Picasso Lighting, we have a program where we make sure all of your reels come from the same lot for each project. This ensures excellent color consistency in large open spaces.
- LED life is rated at 50,000 hours

## Certifications & Warranties

- Limited five-year (50,000 hours) warranty on all products. Limited ten-year (100,000 hours) warranty on all Lutron drivers.
- DLC listed products will have DLC Logo.
- Chicago Plenum products are available upon request.
- Warranty does not cover damage caused by transport, damage caused by using the fixture in an area it is not UL rated for, damage caused by negligence, lack of maintenance, attempts to repair by unqualified or unauthorized personnel, by using non-original accessories/parts, fixtures installed in systems without power surge protection.
- UL and CUL listed for dry and damp locations.
- IBEW USA Union All fixtures are IBEW manufactured and assembled in the USA.
- We manufacture based on approved spec sheets and submittals signed by professionals responsible. Change orders must be in writing and will delay delivery.
- Picasso Lighting must receive in writing any thought to be defective products discovered, no later than 4 weeks from delivery to; [ttoledo@picassoltg.com](mailto:ttoledo@picassoltg.com). Picasso Lighting will send a field technician to the site to evaluate the said defective product. We do accept field repair from licensed electrical contractors but not without a written agreement signed by Picasso Lighting official. Failure to adhere to all warranty and certifications will void any recompense and the warranty.



# Emily EZ-P Continuous

EZ SHIP

**TYPE**

**PROJECT**

Note: Picasso lighting industries, LLC reserves the right to make any design changes which will not affect the overall appearance or performance of the product. All ceilings to be adequately reinforced by others. All fixtures to be wired by licensed electrician only. The information contained herein is the sole property of Picasso Lighting Industries, LLC and may not be used without prior written consent of Picasso Lighting Industries, LLC. The 'USGBC member logo' is a trademark owned by the U.S. Green building council and is used by permission. The logo signifies only that Picasso Lighting Industries, LLC is a USGBC member; USGBC does not review, certify, or endorse the products or services offered by its members.