

Kayla Flush Lens


PENDANT LARGE

TYPE

PROJECT

Overview

- Kayla, kay-luh; a feminine name with Irish, Greek, and Hebrew roots, translating to "slender" and "fair".
- Kayla Series is a popular luminaire for general up-lighting and down-lighting. Extremely unique when designed in brushed, clear coated aluminum.
- DESIGNER SELECTIONS
- Kayla Series has 1 profile size, four and five eighths' inches in height, by two inches in width.
- Kayla Series is available in almost any CCT available in the market, we've selected the most popular, but don't let that stop you from asking for something different
- Kayla Series is available in direct light and direct/indirect light. We can also tune in our drivers to specific lumen output, if required.
- Kayla Series is always available for your project's special customization needs. One example is our Custom Design for the Barclays Center! (view Kayla Flush or Custom Portfolio to see photos)
- Kayla Series qualifies as "Made in America", "American Made" and is part of our ECO sustainable end of life program
- Our Kayla Series is available in Pendant, Surface, and Wall. With the choice of Flush Lens or Dropped Lens
- For all: ies files, pictures, instructions, rfa files, and warranties....scroll to bottom.



Kayla Flush Lens

PENDANT LARGE

TYPE
PROJECT

Ordering Format

PART NUMBER: KAY-PF

Size	Lumens Direct	Lumens Indirect	CCT Available	CRI Available
3 = 3 Feet	D3 = 350 LPF	I3 = 350 LPF	27 = 2700 Kelvins	80 = 80-85 CRI
4 = 4 Feet	D5 = 500 LPF	I5 = 500 LPF	30 = 3000 Kelvins	90 = 90-95 CRI
5 = 5 Feet	D7 = 750 LPF	I7 = 750 LPF	35 = 3500 Kelvins	
6 = 6 Feet	D10 = 1000 LPF	I10 = 1000 LPF	40 = 4000 Kelvins	
8 = 8 Feet	D11 = 1100 LPF	NN = Not Needed	TW = Tunable White 2700-5000 Kelvins	
10 = 10 Feet				
12 = 12 Feet				
CL = Custom Length, add in notes				
SQ = Square, add in notes				
RT = Rectangle, add in notes				
TR = Triangle, add in notes				
Direct Optics	Mounting	Driver / Voltage	Fixture Finish	Canopy/Power Cord Color
FW = Frosted White FW/MC = D- Frosted White/ I-Matte Clear FW/BW = D- Frosted White/ I-Batwing	AC1R = Round 5in Canopy JBox - 5in Support AC1S = Square 5in Canopy JBox - 5in Support ACD1R = Round 5in Canopy JBox - 2in Support Slot Grid ACD1S = Square 5in Canopy JBox - 2in Support Slot Grid ACD2R = Round 5in Canopy JBox - 2in Support T Grid ACD2S = Square 5in Canopy JBox - 2in Support T Grid ACUR = Round 5in Canopy JBox - .5in Support Unistrut ACUS = Square 5in Canopy JBox - .5in Support Unistrut ACRR = Round 5in Canopy JBox - 2in Support 1/4 Rod ACRS = Square 5in Canopy JBox - 2in Support 1/4 Rod	ND 1 = Non-Dim Universal 120VAC ND 2 = Non-Dim Universal 277VAC ZT 1 = 0-10v dimming 120v 1% ZT 2 = 0-10v dimming 277v 1% LE1 = Lutron EcoSystem 1% DLC EE CCR / PWM SoftOnFadeToBlack CC = Custom Controls -add in notes	W = Standard White BK = Standard Black SVR = Standard Silver RAL = Enter RAL # in notes section PA = Plated Aluminum-enter plated finish in notes CW = Standard Wood Finish - see wood PN # enter in notes. SW = Special pattern submitted by designer AA = Anodized Aluminum -enter PN in notes section	CWPW = Canopy White/Power Cord White CWPB = Canopy White/Power Cord Black CBPB = Canopy Black/Power Cord Black CBPW = Canopy Black/Power Cord White
Options				

Kayla Flush Lens

PENDANT LARGE

TYPE
PROJECT

AWN = Lutron Athena
Wireless Node (RF only)
AWNS = Lutron Athena
Wireless Node (with
Sensor)
2C = 2 circuit wiring
for direct indirect
IW = Inverter Wiring
CA = Custom Angle,
add in notes
OS = Occupancy
Sensor
EMD = Emergency
Driver - Battery Backup
120-277VAC

NOTES

ORDER NUMBER:

Kayla Flush Lens

PENDANT LARGE

TYPE

PROJECT

Construction & Mounting

HOUSING

Extruded aluminum housings are supplied in nominal lengths of 4 ft., 6 ft., 8 ft. and 12 ft. Fixtures may be continuously rowed (contact factory for details). Internal components are constructed from min. 20 gauge die-formed steel. Easy access to driver and LED boards. End caps are extruded aluminum. Custom sizes are available.

REFLECTOR

Integral powder-coated LED housing with excessive reflectivity for increased lumen output

FINISH

Standard powder-coated colors are white, black and silver. Custom processed wood finishes, aluminum anodized finishes, chrome/gold plating and custom finishes are available as well. We also accept RAL and Pantone numbers for powder-coating color choices.

OPTICS

Direct component provided with an extruded snap-in frosted acrylic lens formulated for LED light sources. Indirect component LED strips are mounted in an extruded aluminum channel with an integral clear acrylic dust cover.

MOUNTING


Cable mounting with various size canopies and power feeds. If not selected in options, canopy color and cord will be white. Cable uses gripper style locking for field adjustments 48" standard. Canopy mounts to standard J-box. Can also be stem mounted. See options for more information.



Kayla Flush Lens

PENDANT LARGE

TYPE
PROJECT



Kayla Flush Lens

PENDANT LARGE


TYPE

PROJECT

Standard Finishes



White
W



Black
BK



Silver
SVR

Anodized Aluminum

xxxx-B for Aluminum to be Brushed



Anodized Black
AABK




Anodized
DK. Bronze
AADB



Anodized
LT. Bronze
AALB



Anodized
Champagne
AALC



Anodized Clear
AACL



Custom RAL - Custom finishes go to: tiger-coatings.com **Add # in Notes**

Standard Finishes – colors are powder coated and do not add to delivery lead time.

Anodized Aluminum – can be smooth or brushed, color can vary fixture to fixture and adds 2-3 weeks to lead time. Anodized finish is limited in fixture size.

Plated Aluminum – is a mirror finish in chrome and gold and adds 2 weeks to lead time.

Wood Finishes – so realistic, wood finish can add up to 3-4 weeks to lead time.

Plated Aluminum



Antique
Brass
APAB



Aged
Bronze
APBZ



Polished
Chrome
APPC



Polished
Gold
APPG

Wood Finishes



Light Bamboo
LW01



Light Pine
LW02



Teak
LW03



Dark Bamboo
LW04




Dark Cherry
LW05



Brushed Chestnut
LW06



Chestnut
DW01



Dark Chestnut
DW02



Cherry
DW03



Dark Mahogany
DW04



Mahogany
DW05



Walnut Pine
DW06



Dark Walnut Oak
DW07



Consult Factory

Electrical / Driver

- Drivers - Our drivers are specifically selected based on fixture application to ensure ultimate reliability and long life. We use only UL-recognized brands of LED drivers. Our LED drivers feature HPF (high power factor), universal voltage 110 - 277 VAC, and include 0-10V dimming. Please note, 277v has longer distances from power feed to power feed than 120v.
- If required, we can supply premium drivers such as Lutron, Eldoled, and others upon request. Advanced control systems compliant drivers such as POE, DALI, DMX, etc. are also available, please consult factory.
- Rated life (90% survivorship) of 50,000 hours at 50° C max. ambient (and 70° C max. case) temperature. At maximum driver load: Efficiency >84%, PF>0.9, THD
- Our LED drivers feature HPF (high power factor), universal voltage 110 - 277 VAC, and include 0-10V dimming.
- Emergency drivers are factory installed as an option, long life, high temperature, recyclable Ni-Cad battery pack with test switch and charge indicator. EMR is a minimum of 90 minutes of operation to meet code.
- POE - We are working with Molex/Igor POE systems. We can add a POE driver into our fixtures or remote them. Based on the fixture you select, we will notify you (or you can contact the factory) to see if we can install the P-driver or the P-driver needs to be remote. Just add POE1 in the spec and we will advise. Please keep in mind you need to specify a complete POE control system before specifying POE1.

LED Performance

LED Output	CCT Color Temp	Watts	Lumens	Lumens per Watt	CCT Multiplier
Low	3000	5.23 WPF Direct (4 WPF Indirect)	350 LPF	68	2700 = .95
Medium	3000	7.68 WPF Direct (5.8 WPF Indirect)	500 LPF	66 LPW	3000 = 1/3500=1.01/4000=1.03
High	3000	8.6 WPF Indirect only	750 LPF	82 LPW	4000=1.03
Very High	3000	10 WPF	1100 LPF	110 LPW	x

- The table above is a quick reference. When calculating loads make sure you add direct and indirect LPW to get total wattage. Please refer to the photometric report for detailed information.
- Our light engines are precisely designed for optimal operation of LED assemblies.
- Our standard LED's CCT (correlated color temperature) range is 2700K to 4000K. Other CCT values are available upon request.
- We log LED bin codes for each project we supply to ensure color consistency and keep a record of those projects for future reference.
- CRI offered is 80+, and 90+ Note: on 90+ CRI use .85 multiplier
- Tunable white, warm dim, and other special LED colors available.
- Custom Lumens Available
- We design our own printed circuit boards to ensure high luminescence efficiency, low thermal resistance and long-term reliable operation.
- Light engines are easily replaced.
- We use only recognized brand LED's with 3 SDCM (standard deviation color matching) with high color consistency. 2 SDCM available upon request.
- If you require a special LED manufacturer, please contact us. LED chip manufacturers used by Picasso are primarily (but not limited to) Nichia, Cree and Samsung.
- LRP - "LED Reel Program" – LED's for printed circuit boards come on reels' like old 8mm projectors and they're sold in lots just like fabric. At Picasso Lighting, we have a program where we make sure all of your reels come from the same lot for each project. This ensures excellent color consistency in large open spaces.
- LED life is rated at 50,000 hours

Certifications & Warranties

Kayla Flush Lens

PENDANT LARGE

TYPE

PROJECT

- Limited five-year (50,000 hours) warranty on all products. Limited ten-year (100,000 hours) warranty on all Lutron drivers.
- I.C.-rated fixtures are available upon request.
- Chicago Plenum and IC products are available upon request.
- Warranty does not cover damage caused by transport, damage caused by using the fixture in an area it is not UL rated for, damage caused by negligence, lack of maintenance, attempts to repair by unqualified or unauthorized personnel, by using non-original accessories/parts, fixtures installed in systems without power surge protection.
- UL and CUL listed for dry and damp locations.
- IBEW USA Union All fixtures are IBEW manufactured and assembled in the USA.
- We manufacture based on approved spec sheets and submittals signed by professionals responsible. Change orders must be in writing and will delay delivery.
- Picasso Lighting must receive in writing any thought to be defective products discovered, no later than 4 weeks from delivery to; ttoledo@picassoltg.com. Picasso Lighting will send a field technician to the site to evaluate the said defective product. We do accept field repair from licensed electrical contractors but not without a written agreement signed by Picasso Lighting official. Failure to adhere to all warranty and certifications will void any recompense and the warranty.



Note: Picasso lighting industries, LLC reserves the right to make any design changes which will not affect the overall appearance or performance of the product. All ceilings to be adequately reinforced by others. All fixtures to be wired by licensed electrician only. The information contained herein is the sole property of Picasso Lighting Industries, LLC and may not be used without prior written consent of Picasso Lighting Industries, LLC. The 'USGBC member logo' is a trademark owned by the U.S. Green building council and is used by permission. The logo signifies only that Picasso Lighting Industries, LLC is a USGBC member; USGBC does not review, certify, or endorse the products or services offered by its members.